

PRODUCTION PROGRAM





ENGLISH 🏶

PHOENIX

AODD PUMPS

Realized in: PP, PVDF, ALUMINIUM, SS AISI 316, POMc Flow-rate from 7lt/min to 1.000 lt/min Connections from 1/4" to 3". ATEX certification for zone 2 and 1 FOOD version FDA compliant







PHOENIX

ATEX





PHOENIX

SPECIAL FEATURES



TWIN PHOENIX

DRAGON

MECHANICAL SEAL CENTRIFUGAL PUMPS

Realized in: PP and PVDF Flow-Rate: from 6m3/h to 40m3/h Delivery Outlet: from 8mts to 25mts





FLAF

C € EÆ



HELIOS

PERISTALTIC PUMPS

- HELIOS AS
- Max Flow-rate 2800 lt/h Max pressure 4 Bar - HELIOS ASP
- Max Flow-rate 25000 lt/h Max pressure 10 Bar
- HELIOS ATR Max Flow-rate 64000 lt/h - Max pressure 8 Bar



1) FX - FIXED FLOW-RATE 🛛 🕗 VX - VARIABLE FLOW-RATE 🔂 IX - VARIABLE FLOW-RATE WITH INVERTER





LOTUS PURE AODD PUMPS 1/2" - 1" - 1"1/2 - 2" PE - PTFE - PE CONDUCTIVE PTFE CONDUCTIVE



DAMPER PULSATION DAMPENERS

Realized in: PP, PVDF, ALUMINIUM, SS AISI 316, POMc. Applicable on all AODD PUMPS

TYPHOON

VERTICAL CENTRIFUGAL PUMPS

Realized in: PP and PVDF Flow-Rate: from 6m3/h to 40m3/h Delivery Outlet: from 8mts to 25mts Length: from 500mm to 1250mm

C € ER[

COMPASS

MAG DRIVE PUMPS

Realized in: PP, PVDF Flow-rate from 3,5 m3/h to 35 m3/h Delivery outlet from 4mts to 25 mts

MINI COMPASS

Realized in: PP, PVDF Flow-rate from 10 lt/min to 45 lt/min Delivery outlet from 1,5mts to 8 mts





AIR MOTORS


Power from 0.35kW up to 7 kW Speed up to 7000rpm Torque up to 35 Nm



MIXER

VERTICAL AGITATORS ELECTRIC AND PNEUMATIC MOTORS

Realized in: SS AISI 304, 316, PVC COATED, PP COATED Speed from 56 RPM to 1400 RPM Lenght from 600 mm to 3000 mm





DRUM PUMPS Pumps tube made in PP, PVDF, SS, ALU Motor 230 V or Pneumatic Hand Pumps



TAURUS ELECTRO MECHANICAL DOSING PUMPS DIAPHRAGM and PISTON PUMPS











FLUIMAC S.r.l.

Via Brescia I 21049, Tradate (VA) - Italy Tel.:+39 0331 866688 Fax:+39 0331 864870

www.fluimac.com info@fluimac.com

