



15	SCREW	1	STAINLESS STEEL 304	
14	HANDLE	1	ABS	
13	STOP RING	2	PVDF	Used for Flanged End
12	O-RING (E)	1	EPDM,FKM, etc.	
11	O-RING (D)	1	EPDM,FKM, etc.	
10	CUSHION	2	EPDM,FKM, etc.	
9	O-RING (B)	2	EPDM,FKM, etc.	
8	O-RING (A)	2	EPDM,FKM, etc.	
7	SEAT	2	PTFE	
6	STEM	1	PVC,CPVC,PP,PVDF	
5	UNION NUT	2	PVC,CPVC,PP,PVDF	
4e	END CONNECTOR (SPIGOT)	2	PP,PVDF	BUTT END
4d	END CONNECTOR (THREADED)	2	PVC,CPVC,PP,PVDF	
4c	END CONNECTOR (SOCKET)	2	PVC,CPVC,PP,PVDF	
4b	END CONNECTOR (FLANGED)	2	PVC,CPVC,PP,PVDF	
3	CARRIER	2	PVC,CPVC,PP,PVDF	
2	BALL	1	PVC,CPVC,PP,PVDF	
1	BODY	1	PVC,CPVC,PP,PVDF	
No.	DESCRIPTION	No.REQ'D	MATERIAL	REMARKS

FOR REFERENCE ONLY
ASAHI/AMERICA

THIS DRAWING AND ALL INFORMATION
HEREON IS THE PROPERTY OF
ASAHI/AMERICA. ANY COPYING,
REPRODUCTION OR UNAUTHORIZED USE
IS FORBIDDEN WITHOUT WRITTEN
CONSENT.

	NAME	DATE
DR	KENICHI MIYAZAKI	8/26/02
APPD	DAVE HURLEY	8/26/02
PROD	LEO LESTER	8/26/02
WO#/SO#		
FILE		

ASAHI/AMERICA

ISO 9001 CERTIFIED

35 GREEN STREET, P.O. BOX 653, MALDEN, MA.



BALL VALVE TYPE 21
EXPLODED VIEW
2-1/2" THRU. 4"

SIZE	A	DWG. NO.	0098BV	REV	B
SCALE	NTS		SHEET 1 OF 1		